


# MEC-COM-M154

*Mini PCI-e 2-port RS-232 and 2-port RS232/422/485 serial board with power input*



- PCI Express x 1 compliant
- Top serial transmission performance up to 921.6 Kbps baud rate
- FIFO 128 Bytes, 15 KV ESD protections on board
- H/W, S/W automate flow control supported
- RS-232/422/485 mode selectable by DIP switches setting
- Each port supports 5V or 12V power output by jumper setting



## Overview

MEC-COM-M154 is a serial communication card for embedded PC. The card follows the Mini PCI-e standard which is complaint with PCI Express x 1 classification and small form factor (30.00 x 50.95 mm). This board fits in any host computer that has Mini PCI-e card slots.

### Top Performance

MEC-COM-M154 has 2x RS-232 and 2x RS-232/422/485 serial ports, each individual port supports 921.6 Kbps baud rate. The combination features 15KV ESD protection, FIFO 128 Bytes, HW/SW automated flow control and extended operating temperature which enhances the board's reliability and performance.

### High Usability

MEC-COM-M154 is designed with flexibilities for many different applications. The Serial RS-232/422/485 mode can be configured by DIP switches, the power output can be configured by jumper. The accessories (bracket, connection / power input cable) are included in the standard package.

## Specifications

### Hardware

**Controllers:** OXPcie954 (16C550C compatible)

**Bus:** PCI Express X1

### Interface (Connector)

**RS-232:** 2 (DB9 male)

**RS-232 / 422 / 485:** 2 (DB9 male)

### Serial Line Protection

**ESD Protection:** 15 KV on board

### Serial Port Power

**Voltage Select:** 5V or 12V

### Performance

**Baud Rate:** Asynchronous baud rates up to 921.6 Kbps

### Serial Communication Parameters

**Data Bits:** 5, 6, 7, 8

**Stop Bits:** 1, 1.5, 2

**Parity:** • No Parity bit • Odd Parity bit  
• Even Parity bit • Parity bit forced to 1  
• Parity bit forced to 0

**Flow Control:** RTS/CTS, XON/XOFF

### Serial Signals

**RS-232:** TXD, RXD, RTS, CTS, DTR, DSR, DCD, GND

### Driver Support

**Operating Systems:** Win 2003, Win XP, Win Vista, Win 7

### Power Requirement

**Power Consumption:** 424mA@3.3V

### Dimensions

**Width x Length (mm):** 30.00 x 50.95

### Environmental Limits

**Operating Temperature:** -20°C ~ 70°C

**Storage Temperature:** -20°C ~ 85°C

**Humidity:** 5% ~ 95%

### Regulatory Approvals

**EMC:** CE, FCC

**EMI:** EN 55022, EN61000-3-2, EN61000-3-3,  
FCC Part 15 Subpart B

Class B

**EMS:** En 55024, IEC 61000-4-2, IEC 61000-4-3,  
IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6,  
IEC 61000-4-8, IEC 61000-4-11


### Reliability

**MTBF:** 1,712,123 hr

**Warranty:** 3 years

## Dimensions

Unit: mm



## Package Checklist

- Mini PCI-e Card x 1
- Bracket x 2
- 20Pin Internal Cable w/ two DB9 Male Connectors (30cm) x 2
- 4Pin Power Input Cable (30cm) x 1
- Quick Installation Guide (Printed) x 1
- Driver CD x 1



## Ordering Information

### Available Models

MEC-COM-M154

Mini PCI-e 2-port RS-232 and 2-port RS232/422/485 serial board with power input