



# EP2C622D16-2T



3647




10Gbase-T




Slimline

16 DIMM Slots, Supports Six Channel DDR4 2933/2666/2400/2133 RDIMM and LR DIMM, Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)



2 x M.2 (Form Factor: 2230/2242/2260/2280/22110, PCIe 3.0(x4)/SATA3 6.0Gb/s)



## Application

- Web Server and Virtual Machine
- Cloud Computing
- Compact Network Appliance

Purley  
Socket P 3647

		EP2C622D16-2T
<b>Form Factor</b>		EEB(12x13")
<b>Processor Support</b>		Dual Socket P LGA 3647, Supports 2 <sup>nd</sup> Gen. Intel® Xeon® Scalable Processors / Intel® Xeon® Scalable Processors
<b>Chipset</b>		Intel® C622
<b>Memory</b>		Six Channel, 16 DIMMs, DDR4 2933/2666/2400/2133 RDIMM and LR DIMM, Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)
<b>Storage</b>	Intel PCH OCuLink for U.2	Intel® C622: 14 x SATA3( 8 port from miniSAS HD, 2port by SATA CONN, 2port from SATA DOM, 2 port from M.2) 2 (Slimline x8 from CPU1, OCuLink x4 from CPU1)
<b>Expansion Slots</b>		4 x PCIe3.0 x16
<b>Ethernet</b>	LAN Controller LAN Port	Intel® X550-AT2 RJ45: 2+1(IPMI)
<b>System management</b>	BMC Controller IPMI dedicated LAN	ASPEED 2500: IPMI (Intelligent Platform Management Interface) 2.0 with Ikmv, vMedia support) 1 x Realtek RTL8211E for Dedicated Management GLAN PIN
<b>USB 3.0</b>		6(4 from rear IO, 2 via header)
<b>USB 2.0</b>		1(Type A)
<b>M.2</b>		2(2230/2242/2260/2280/22110, PCIe 3.0(x4)/SATA3 6.0Gb/s)