

# PE-5004

Intel® XL710 4-port 10GigE PoE+ PCI Express Expansion Card

10GigE

- Intel® XL710 10GBASE-T Ethernet Controller and Intel® X557 PHY supports 4-port independent 10GigE PoE+ LAN, up to 10Gbps data rate
- PCI Express x8 interface, PCIe 3.0 supports up to 8.0 GT/s
- IEEE 802.3at Power over Ethernet (PoE+), up to 25.5W Power Output at 48V DC per port, with PoE+ On/Off Control
- IEEE 1588 Precision Time Protocol (PTP) and IEEE 802.1AS Precision Timing Synchronization compliant
- Up to 15.5KB Jumbo Frame, Link Aggregation
- Supports IEEE 802.3az Energy Efficient Ethernet (EEE) and DMA Coalescing Power Management Features
- -25°C to 55°C Operating Temperature

Scientific Research



Goal-line Technology





Deep Learning



Real-time Inspection



## Applications



## Specifications

### Ethernet

Interface	PCI Express x8
Controller	Intel® Ethernet Controller XL710
Controller Qty	1
PHY	Intel® X557
PHY Qty	1
Data Rate	10Gbps/1Gbps/100Mbps
Number of Port	4
Jump Frame	Up to 15.5KB supported
Link Aggregation (LAG)	Present
PoE Standard	IEEE 802.3at compliant

### Power Requirement

Output	- 4 RJ45 Connector - 4 LED for PoE On/Off Mode - Up to 25.5W Power Output at 48V DC per port
Power Connector	1 4-pin 12V Power Connector

### Mechanical

Dimension (W x L)	168mm x 111mm (6.6" x 4.4")
Bracket	Full height

### Software Support

OS	Windows 10, Linux
----	-------------------

\* The rights of all brand names, product names and trademarks belong to their respective owners.  
Copyright © 2019 Vecow Co., Ltd. All rights reserved.

### Environment

Operating Temperature	-25°C to 55°C with air flow (-40°F to 131°F)
Storage Temperature	-40°C to 85°C (-40°F to 185°F)
Humidity	5% to 95% Humidity, non-condensing
Relative Humidity	95% @ 55°C
EMC	CE, FCC

## Order Information

Model	Description
PE-5004	Intel® XL710 4-CH PCI Express Card with 10GigE PoE <sup>+</sup>

## Dimensions & Drawing

Unit : mm (inch)

