

2U12L2S-ROME/2T



Storage

3200


10Gbase-T



12x3.5" HDD/SSD bays

Application

- Software-defined Storage
- Data Analytics



General Purpose

2U12L2S-ROME/2T

CPU	Socket	1 SP3(LGA4094), supports AMD EPYC 7002 Series Processors
DIMM	Capacity	8 DDR4 DIMM slots (1DPC), Supports DDR4 R-DIMM up to 64GB each/ LR-DIMM up to 256GB each; max. 3200MHz
System Physical Status	Form Factor	2U Rackmount
	Chassis Dimension	482.6 x 625 x 87 mm (includes ears)
Front Panel	Buttons	Power button w/LED, UID button, NMI button (left ear)
	LEDs	LAN1 and LAN2, system fault
	USB	1 Type-A USB3.1 Gen1 (right ear)
Rear IO	RJ45	2 RJ45 (10GbE) via Intel® X550-AT2 1 dedicated IPMI via AST2500
	USB	2 USB3.2 Gen1 (5Gbps)
	Video	1 DB15 (VGA) via AST2500
	Others	1 DB9 COM port, 1 UID button w/ LED
	Expansion Slots	Rear
Storage	External Drive Bay	12 Hot-swappable 3.5" (SATA 6Gb/s)
	Internal Storage	1 M-key (PCIe3.0x4/ SATA); Form factor: 2280 2 SFF 2.5" drive bay
Power Supply	Module	1+1, 80-PLUS Platinum, 800W CRPS
System Cooling	Fan	4 80x38 mm fans
Management		ASPEED BMC AST2500
Security		TPM by optional accessory (TPM2-S)