

# 4U 36-Bay Performance-optimized Storage Server



## 4U36L2S-C621

## 4U36L2S-C612



DDR4



Storage



SAS3 12Gb/s

### Application

- Cloud Datacenter Storage
- Virtual Tape Library



6 x 40\*56 mm PWM Easy-Swap Fans

1200W Redundant PSU (1+1)

2 x Hot-Swap Drive Bay 2.5"



Front control panel

USB 3.0 x2



General Purpose Storage



### 4U36L2S-C621



### 4U36L2S-C612

System Physical Status	Form Factor	4U Rackmount	4U Rackmount
	Chassis Dimension	625mm X 482.6mm X 174.3 mm	625mm X 482.6mm X 174.3 mm
	Support MB Size	EP2C612D16SM-2T(EEB, 12" x 13")	EP2C622D16-2T(EEB, 12" x 13")
Front Panel	Buttons	Power On Button, UID, Reset, NMI, System Reset Button	Power On Button, UID, NMI, System Reset Button
	LEDs	LAN, HDD LED, System Fail Activity LEDs	LAN, HDD LED, System Fail Activity LEDs
	I/O Ports	2 x USB 3.0 ports	2 x USB 3.0 ports
Storage	External	36 x Hot-Swap Drive Bay 2.5"/3.5" SATA HDD (6Gb/s) or 36 x SAS (12Gb/s) (depends on RAID card) 2 x Hot-Swap Drive Bay 2.5" (in the rear side)"	36 x Hot-Swap Drive Bay 2.5"/3.5" SATA HDD (6Gb/s) or 36 x SAS (12Gb/s) (depends on RAID card) 2 x Hot-Swap Drive Bay 2.5" (in the rear side)"
System cooling	Fan	7 x 80*38 mm PWM Hot-Swap Fans	6 x 40*56 mm PWM Easy-Swap Fans
Power Supply	Capacity	1 (1+1), Redundant	2 (1+1), Redundant
	Output Watts	1200W	1200W
	Efficiency	Platinum	Platinum